

AMINOL PREMIUM PMG5 5W40

PASSENGER CAR ENGINE OIL

Description and Application

Aminol Premium PMG5 5W40 multigrade engine oil is semisynthetic product blended according to the latest advanced lubricant technology and designated for lubrication of today's engines in passenger cars, light trucks and vans.

Aminol Premium PMG5 5W40 multigrade engine oil is recommended for high performance gasoline and heavy-duty diesel engines of passenger cars operated in a wide temperature range and variable conditions. This is especially fit for use in gasoline and diesel engines, naturally aspirated or turbocharged, fuel injector type, multiple valve system, etc.

Benefits

- Very good detergent/dispersant properties for maximum engine cleanliness
- Excellent oxidation stability to minimize viscosity changes during service
- Confident and dependable protection against wear, corrosion and deposit formation
- Constant and stable lubricating film over a wide temperature range and under heavy loads

Specification

	SAE 5W-40
API	SL/CF

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	ASTM D 4052	0.856
Kinematic Viscosity at 100°C, mm ² /s	ASTM D 445	14.4
Kinematic Viscosity at 40°C, mm ² /s	ASTM D 445	87.0
Viscosity Index	ASTM D 2270	172
Flash point COC, °C	ASTM D 92	234
Pour point, °C	ASTM D 97	-39
TBN (HClO ₄), mg KOH/g	ASTM D 2896	10.0
Sulfated Ash, %	ASTM D 874	1.2

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.aminol.az

Packages

1L, 4L, 5L, 20L, 200L